Northeastern Midget Association Annual Car and Driver Safety Evaluation Guide ref 3.4

NOTE: Car and Driver Safety conformity does not authorize technical compliance. ref 7.2
Safety items, their proper use and maintenance are the ultimate responsibility of the car owner and driver. ref 3.2

♦ Seat *ref 7.12*

Car Related Items

♦ Chassis / Roll Cage ref 7.5

Helmet must not protrude out of cage	Full containment or authorized other
Recommend minimum 3" helmet clearance	Securely mounted, maximum 30° angle
♦ Nerf Bars / Bumpers ref 7.5	♦ Fuel Tank / Fuel Lines ref 7.13, 7.24
Recommend minimum #10 mounting bolt	Securely mounted Locking cover
at all chassis contact points	Plastic shell, rubber bladder
at all original points	Functioning vent / rollover valve
♦ Steering Components ref 7.4	Tank functioning and accessible shut-off
Visual Inspection, recommend Article VII 7.4 Rule	
	♦ Cockpit Safety ref 7.24, 7.26
♦ Steering Wheel Quick Release ref 7.25	Recommend steering wheel pad, knee brace / padding
Functions properly	Driver accessible fuel shut-off and engine kill switch
ranctions property	No sharp objects
♦ Wing ref 7.29	Tro sharp objects
Securely fastened, no loose side panels	♦ Belts ref 7.8
Securety rusteries, no loose side punels	Recommend 3 inch minimum / 5 point
♦ Belly Pan <i>ref 7.31, 7.41</i>	Labeled SFI 16.1 or 16.5
Securely fastened, no holes, fixed heel blocks	Not older than 4 years
Securety rasteried, no notes, fixed freel blocks	Release functions properly
♦ Ballast / Added Weight ref 7.5	Attached properly and securely
Securely fastened within frame rails	No fraying
Securety rastened within frame rans	No Iraying
♦ Throttle Linkage ref 7.27	♦ Brakes ref 7.22
Minimum 2 return springs, no binding	Functioning 4-wheel brakes
Driver Relate ♦ Firesuit ref 6.3	ed Items
Minimum double layer, SFI 3.2A/5	Type Man. Date
No visible holes, tears, contaminations	Minimum SFI Spec 38.1
Recommend Nomex Underwear SFI Spec 3.3	
	♦ Helmet ref 6.4
♦ Gloves ref 6.3	Full face, not older than 2005 Snell 31.1
Recommend minimum SFI Spec 3.3	Shield and pivots in good condition
No holes or tears	George George George
	♦ Shoes ref 6.3
♦ Arm Restraints ref 6.3	No holes in soles or uppers
No fraying in material	Socks required
Team Possesses: Minimum 5 Lb. dry chemical or Co2	2 fire extinguisher ref 7.3 First Aid Kit
NEMA Car #: Car Owner:	NEMA Driver:
NEMA Lite Car #: Car Owner:	NEMA Lite Driver:
NEMA Official / Inspector:	Date:
Recommendations:	